

[2019 Multi-University Training Contest 1]

[比赛网址](#)

训练详情

- 时间:2020-5-17 13:00~18:00
- rank:
- 完成情况：

题解

A Rush Hour Puzzle

题意

一个大家都玩过的游戏，求步数

题解

solved by fyh

把6*6哈希压成一个状态，然后直接bfs暴力搜 代码写的过于丑，但是基本都是复制粘贴的。

```
#include<bits/stdc++.h>
#include<map>
using namespace std;
#define mem(a,b) memset(a,b,sizeof(a))
typedef long long LL;
typedef unsigned long long ULL;
typedef pair<int,int> PII;
#define X first
#define Y second
inline int read()
{
    int x=0,f=1;char c=getchar();
    while(!isdigit(c)){if(c=='-')f=-1;c=getchar();}
    while(isdigit(c)){x=x*10+c-'0';c=getchar();}
    return x*f;
}
struct State
{
    int st[10][10];
```

```
State() {mem(st,0);}
ULL Hash()
{
    ULL res=0;
    for(int i=0;i<6;i++)
        for(int j=0;j<6;j++)
            res=(res+st[i][j])*107;
    return res;
}
};

map<ULL,int> vis;
map<ULL,int> dis;
queue<State> Q;
int main()
{
    State init;
    for(int i=0;i<6;i++)
        for(int j=0;j<6;j++)
            init.st[i][j]=read();
    Q.push(init);
    ULL hinit=init.Hash();
    vis[hinit]=1;
    dis[hinit]=0;
    while(Q.size())
    {
        State now=Q.front();Q.pop();
        ULL hnow=now.Hash();
        if(dis[hnow]>8) return puts("-1"),0;
        if(now.st[2][5]==1 && now.st[2][4]==1) return
printf("%d\n",dis[hnow]+2),0;
        for(int i=0;i<6;i++)
            for(int j=0;j<6;j++)
            {
                if(now.st[i][j] && j+1<6 && now.st[i][j]==now.st[i][j+1] &&
(now.st[i][j+1]!=now.st[i][j+2] || j+2>=6) && (now.st[i][j-1]!=now.st[i][j] ||
j<=0))//横2车
                {
                    if(j>0 && !now.st[i][j-1])//左移
                    {
                        State tmp=now;
                        tmp.st[i][j-1]=now.st[i][j];
                        tmp.st[i][j+1]=0;
                        ULL htmp=tmp.Hash();
                        if(!vis[htmp])
                        {
                            dis[htmp]=dis[hnow]+1;
                            vis[htmp]=1;
                            Q.push(tmp);
                        }
                    }
                }
            }
    }
}
```

```

        if(j+2<6 && !now.st[i][j+2])
        {
            State tmp=now;
            tmp.st[i][j+2]=now.st[i][j];
            tmp.st[i][j]=0;
            ULL htmp=tmp.Hash();
            if(!vis[htmp])
            {
                dis[htmp]=dis[hnow]+1;
                vis[htmp]=1;
                Q.push(tmp);
            }
        }//右移
    }
    else if(now.st[i][j] && j+2<6 &&
now.st[i][j]==now.st[i][j+1] && now.st[i][j+1]==now.st[i][j+2])//横3车
    {
        if(j>0 && !now.st[i][j-1])//左移
        {

            State tmp=now;
            tmp.st[i][j-1]=now.st[i][j];
            tmp.st[i][j+2]=0;
            ULL htmp=tmp.Hash();
            if(!vis[htmp])
            {
                dis[htmp]=dis[hnow]+1;
                vis[htmp]=1;
                Q.push(tmp);
            }
        }
        if(j+3<6 && !now.st[i][j+3])
        {
            State tmp=now;
            tmp.st[i][j+3]=now.st[i][j];
            tmp.st[i][j]=0;
            ULL htmp=tmp.Hash();
            if(!vis[htmp])
            {
                dis[htmp]=dis[hnow]+1;
                vis[htmp]=1;
                Q.push(tmp);
            }
        }
    }//右移
}
else if(now.st[i][j] && i+1<6 &&
now.st[i][j]==now.st[i+1][j] && (now.st[i+1][j]!=now.st[i+2][j] || i+2>=6)
&& (now.st[i-1][j]!=now.st[i][j] || i<=0))//竖2车
{
    if(i>0 && !now.st[i-1][j])//上移
    {

```

```
        State tmp=now;
        tmp.st[i-1][j]=now.st[i][j];
        tmp.st[i+1][j]=0;
        ULL htmp=tmp.Hash();
        if(!vis[htmp])
        {
            dis[htmp]=dis[hnow]+1;
            vis[htmp]=1;
            Q.push(tmp);
        }
    }
    if(i+2<6 && !now.st[i+2][j])
    {
        State tmp=now;
        tmp.st[i+2][j]=now.st[i][j];
        tmp.st[i][j]=0;
        ULL htmp=tmp.Hash();
        if(!vis[htmp])
        {
            dis[htmp]=dis[hnow]+1;
            vis[htmp]=1;
            Q.push(tmp);
        }
    }
    } //右移
}
else if(now.st[i][j] && i+2<6 &&
now.st[i][j]==now.st[i+1][j] && now.st[i+1][j]==now.st[i+2][j]) //竖3车
{
    if(i>0 && !now.st[i-1][j]) //上移
    {
        State tmp=now;
        tmp.st[i-1][j]=now.st[i][j];
        tmp.st[i+2][j]=0;
        ULL htmp=tmp.Hash();
        if(!vis[htmp])
        {
            dis[htmp]=dis[hnow]+1;
            vis[htmp]=1;
            Q.push(tmp);
        }
    }
    if(i+3<6 && !now.st[i+3][j])
    {
        State tmp=now;
        tmp.st[i+3][j]=now.st[i][j];
        tmp.st[i][j]=0;
        ULL htmp=tmp.Hash();
        if(!vis[htmp])
        {
            dis[htmp]=dis[hnow]+1;
            vis[htmp]=1;
            Q.push(tmp);
        }
    }
}
```

```
        vis[htmp]=1;
        Q.push(tmp);
    }
}
}//右移
}
}
puts("-1");
return 0;
}
```

C Are They All Integers?

solved by hxm

题意

大水题

题解

略

D Tapioka

solved by wxg

题意

删掉一个字符串序列中的指定的字符串

题解

无敌水题，略

E The League of Sequence Designers

solved by wxg&hxm

题意

给定一个数字序列，求最大的连续和乘以长度。

现在给出一个错误的做法，错误做法仅计算最大连续和来更新答案

求构造出一个长度大于\$|I|\$小于\$2000\$的序列，使得错误答案和正确答案相差正好为\$k\$

题解

分析发现，只要在最大连续和的串前加上一个负数，那么这个做法就会出错，现在要构造出两种答案相差\$k\$

由于最大长度为\$1999\$，不妨就构造长度为\$1999\$的序列，第一位为\$-1\$，剩下为非负数，和为\$a\$则有

$$(a - 1) \times 1999 - a \times 1998 = k$$

即\$a = k + 1999\$算出\$a\$后，分配给剩下每一位即可

```
#include<algorithm>
#include<iostream>
#include<cstdlib>
#include<cstring>
#include<cstdio>
#include<vector>
#include<queue>
#include<cmath>
#include<map>
#include<set>
#define LL long long int
#define REP(i,n) for (int i = 1; i <= (n); i++)
#define Redge(u) for (int k = h[u].to; k; k = ed[k].nxt)
#define cls(s,v) memset(s,v,sizeof(s))
#define mp(a,b) make_pair<int,int>(a,b)
#define cp pair<int,int>
using namespace std;
const int maxn = 100005, maxm = 100005, INF = 0x3f3f3f3f;
inline int read(){
    int out = 0, flag = 1; char c = getchar();
    while (c < 48 || c > 57){if (c == '-') flag = 0; c = getchar();}
    while (c >= 48 && c <= 57){out = (out << 1) + (out << 3) + c - 48; c = getchar();}
    return flag ? out : -out;
}
int K,L;
int ans[maxn];
void work(){
    int sum = 1999 + K;
```

```

printf("1999\n");
printf("-1");
for (int i = 1; i <= 1997; i++) printf(" %d",sum / 1998);
printf(" %d\n",sum - sum / 1998 * 1997);
}
int main(){
    int T = read();
    while (T--){
        K = read(); L = read();
        if (L >= 2000) puts("-1");
        else work();
    }
    return 0;
}

```

H Mining a

solved by fyh&hxm

题意

$$\frac{1}{n} = \frac{1}{a} \oplus \frac{1}{b}$$

给定 \$n\$ 和 \$b\$ 是任意的，求最大的 \$a\$ 使等式成立

题解

化简得 \$b = n + \frac{n^2}{a \oplus b - n}\$

枚举分母即可

```

#include<algorithm>
#include<iostream>
#include<cstdlib>
#include<cstring>
#include<cstdio>
#include<vector>
#include<queue>
#include<cmath>
#include<map>
#include<set>
#define LL long long int
#define REP(i,n) for (int i = 1; i <= (n); i++)
#define Redge(u) for (int k = h[u].to; k; k = ed[k].next)
#define cls(s,v) memset(s,v,sizeof(s))
#define mp(a,b) make_pair<int,int>(a,b)

```

```
#define cp pair<int,int>
using namespace std;
const int maxn = 100005,maxm = 100005,INF = 0x3f3f3f3f;
inline int read(){
    int out = 0,flag = 1; char c = getchar();
    while (c < 48 || c > 57){if (c == '-') flag = 0; c = getchar();}
    while (c >= 48 && c <= 57){out = (out << 1) + (out << 3) + c - 48; c = getchar();}
    return flag ? out : -out;
}
LL n,a,b,N,ans;
int main(){
    int T = read();
    while (T--){
        ans = 0;
        n = read(); N = n * n;
        LL t;
        for (int i = 1; i < n; i++){
            if (N % i == 0){
                //1
                t = i;
                b = N / t + n;
                a = (t + n) ^ b;
                ans = max(ans,a);
                //2
                t = N / i;
                b = N / t + n;
                a = (t + n) ^ b;
                ans = max(ans,a);
            }
        }
        printf("%I64d\n",ans);
    }
    return 0;
}
```

J Automatic Control Machine

solved by hxm

题意

给定若干个集合，使用最少的集合并成全集

题解

bitset状压dp一下就好了



K Automatic Control Machine

solved by wxg

题意

合并果子，数据还特小，题解略

训练实况

训练总结

改进

From:
<https://wiki.cvbbacm.com/> - CVBB ACM Team

Permanent link:
https://wiki.cvbbacm.com/doku.php?id=2020-2021:teams:die_java:front_page_springtraining6&rev=1590165629

Last update: 2020/05/23 00:40

