

生成函数理论 5

基本应用

例 1

P2000 拯救世界

依照题意可列出 10 个条件的生成函数 $f_i(x)$ 将它们相乘再化简即可。

- $f_1(x) = (1 + x^6 + x^{12} + \dots) = \frac{1}{1 - x^6}$
- $f_2(x) = (1 + x + x^2 + \dots + x^9) = \frac{1 - x^{10}}{1 - x}$
- $f_3(x) = (1 + x + x^2 + \dots + x^5) = \frac{1 - x^6}{1 - x}$
- $f_4(x) = (1 + x^4 + x^8 + \dots) = \frac{1}{1 - x^4}$
- $f_5(x) = (1 + x + x^2 + \dots + x^7) = \frac{1 - x^8}{1 - x}$
- $f_6(x) = (1 + x^2 + x^4 + \dots) = \frac{1}{1 - x^2}$
- $f_7(x) = (1 + x) = \frac{1 - x^2}{1 - x}$
- $f_8(x) = (1 + x^8 + x^{16} + \dots) = \frac{1}{1 - x^8}$
- $f_9(x) = (1 + x^{10} + x^{20} + \dots) = \frac{1}{1 - x^{10}}$
- $f_{10}(x) = (1 + x + x^2 + x^3) = \frac{1 - x^4}{1 - x}$

$$f(x) = \prod_{i=1}^{10} f_i(x) = \frac{1}{(1-x)^5} = \sum_{n=0}^{\infty} \binom{n+4}{4} x^n$$

$$\text{ans}_n = \binom{n+4}{4} = \frac{(n+4)(n+3)(n+2)(n+1)}{24}$$

由于 $10^{100000} \leq n < 10^{100001}$ 需要用高精度，正解是用 NTT 用 Python 会 TLE 但是竟然可以用 Ruby AC

Ruby 代码：

```
n=Integer(gets)
puts (n+4)*(n+3)*(n+2)*(n+1)/24
```

C++ 代码：

```
#include<bits/stdc++.h>
using namespace std;
const int N=5e6+5,P=998244353,G=3,Gi=332748118;
typedef long long ll;
int rev[N];
char s[N];
ll n1[N],n2[N],n3[N],n4[N];
ll fastpow(ll x,ll y){
```

```
ll ret=1;
for(;y;y>=1,x=x*x%P)
    if(y&1) ret=ret*x%P;
return ret;
}
void NTT(ll *y,int len,int on){
for(int i=0;i<len;i++)
    if(i<rev[i])
        swap(y[i],y[rev[i]]);
for(int mid=1;mid<len;mid<=<1){
ll wn=fastpow(on==1?G:Gi,(P-1)/(mid<<1));
for(int j=0;j<len;j+=(mid<<1)){
ll w=1;
for(int k=0;k<mid;k++,w=w*wn%P){
ll u=y[j+k],t=w*y[j+k+mid]%P;
y[j+k]=(u+t)%P;
y[j+k+mid]=(u-t+P)%P;
}
}
}
}
ll c[N];
void mul(ll *a,ll *b,int &n,int &m){
for(int i=0;i<=n;i++) a[i]=0;
for(int i=0;i<=m;i++) b[i]=0;
int len=1,l=0;
while(len<=n+m) len<=<1,l++;
for(int i=0;i<len;i++) rev[i]=(rev[i>>1]>>1)|((i&1)<<(l-1));
NTT(a,len,1);
NTT(b,len,1);
for(int i=0;i<len;i++) a[i]=a[i]*b[i]%P;
NTT(a,len,-1);
ll inv=fastpow(len,P-2);
memset(c,0,sizeof(c));
for(int i=0;i<=n+m;i++){
a[i]=a[i]*inv%P;
c[i]+=a[i];
c[i+1]+=c[i]/10;
c[i]%=10;
}
if(c[n+m+1]) n++;
for(int i=0;i<=n+m;i++) a[i]=c[i];
n=n+m;
}
ll ans[N];
int main(){
scanf("%s",s);
int n=strlen(s);
n--;
int len1=n,len2=n,len3=n,len4=n;
for(int i=0;i<=n;i++) n1[i]=n2[i]=n3[i]=n4[i]=s[n-i]-'0';
```

```
n1[0]+=1;
n2[0]+=2;
n3[0]+=3;
n4[0]+=4;
for(int i=0;i<=n;i++){
    n1[i+1]+=n1[i]/10;
    n1[i]%=10;
    n2[i+1]+=n2[i]/10;
    n2[i]%=10;
    n3[i+1]+=n3[i]/10;
    n3[i]%=10;
    n4[i+1]+=n4[i]/10;
    n4[i]%=10;
}
if(n1[n+1]) len1++;
if(n2[n+1]) len2++;
if(n3[n+1]) len3++;
if(n4[n+1]) len4++;
mul(n1,n2,len1,len2);
mul(n1,n3,len1,len3);
mul(n1,n4,len1,len4);

ll p=0;
int lenans=0;
for(int i=len1;i>=0;i--){
    p=p*10+n1[i];
    ans[i]=p/24;
    p%=24;
    if(ans[i]&&!lenans) lenans=i;
}
for(int i=lenans;i>=0;i--)
    printf("%lld",ans[i]);
return 0;
}
```

From: <https://wiki.cvvbacm.com/> - CVBB ACM Team

Permanent link: https://wiki.cvvbacm.com/doku.php?id=2020-2021:teams:legal_string:lgwza:%E7%94%9F%E6%88%90%E5%87%BD%E6%95%B0%E7%90%86%E8%AE%BA_5_%E4%B8%80%E4%BA%9B%E4%BE%8B%E5%AD%90&rev=1613912378

Last update: 2021/02/21 20:59