

## POJ 1191

$8 \times 8$  矩阵切  $n-1$  次成  $n$  块（每切一次挑其中一半继续切），问最小均方差


题解：均方差的一种形式是  $\sqrt{\frac{\sum\{x_i^2\}}{n} - \{\bar{x}\}^2}$  平均值其实是固定的，所以最小化  $\sum\{x_i^2\}$  二维区间dp

有精度问题要用c++提交才能过g++不行。。恐怖

```
#include<iostream>
#include<cstdio>
#include<cstring>
#include<cmath>
#include<cstdlib>
using namespace std;
int n,a[9][9];
int f[9][9][9][9][16],pre[9][9];
int dp(int x1,int y1,int x2,int y2,int k)
{
    if(k==0)
        f[x1][y1][x2][y2][k]=(pre[x2][y2]-pre[x2][y1-1]-pre[x1-1][y2]+pre[x1-1][y1-1])*(pre[x2][y2]-pre[x2][y1-1]-pre[x1-1][y2]+pre[x1-1][y1-1]);
        if(x1==x2&&y1==y2)f[x1][y1][x2][y2][k]=a[x1][y1]*a[x1][y1];
        if(f[x1][y1][x2][y2][k]<0x3f3f3f3f)return f[x1][y1][x2][y2][k];
        for(int i=x1;i<x2;i++)
        {
            f[x1][y1][x2][y2][k]=min(f[x1][y1][x2][y2][k],dp(x1,y1,i,y2,0)+dp(i+1,y1,x2,y2,k-1));
            f[x1][y1][x2][y2][k]=min(f[x1][y1][x2][y2][k],dp(x1,y1,i,y2,k-1)+dp(i+1,y1,x2,y2,0));
        }
        for(int i=y1;i<y2;i++)
        {
            f[x1][y1][x2][y2][k]=min(f[x1][y1][x2][y2][k],dp(x1,y1,x2,i,0)+dp(x1,i+1,x2,y2,k-1));
            f[x1][y1][x2][y2][k]=min(f[x1][y1][x2][y2][k],dp(x1,y1,x2,i,k-1)+dp(x1,i+1,x2,y2,0));
        }
        return f[x1][y1][x2][y2][k];
    }
}
int main()
{
    while(~scanf("%d",&n))
    {
        memset(pre,0,sizeof(pre));
        memset(f,0x3f,sizeof(f));
        for(int i=1;i<=8;i++)
        {
            for(int j=1;j<=8;j++)
            {
```

```
scanf("%d",&a[i][j]);
pre[i][j]=pre[i][j-1]+pre[i-1][j]-pre[i-1][j-1]+a[i][j];
    }
}
printf("%.3lf\n",sqrt(dp(1,1,8,8,n-1)*1.0/n-
(1.0*pre[8][8]/n)*(1.0*pre[8][8]/n)));
}
return 0;
}
```

From:  
<https://wiki.cvbbacm.com/> - CVBB ACM Team

Permanent link:  
[https://wiki.cvbbacm.com/doku.php?id=2020-2021:teams:wangzai\\_milk:weekly:poj\\_1191&rev=1588996765](https://wiki.cvbbacm.com/doku.php?id=2020-2021:teams:wangzai_milk:weekly:poj_1191&rev=1588996765) 

Last update: **2020/05/09 11:59**